

dB-3911 TWT Amplifier



4.0kW Pulsed
7.5 – 18 GHz



The dB-3911 power-combined TWT Amplifier (TWTA) uses two wideband, periodic permanent magnet (PPM)-focused TWTs to amplify CW, AM, FM or pulse-modulated signals. Compared to a single TWT approach, the dB-3911 provides higher saturated output power and improved harmonic performance. In addition, dB Control minimizes losses from power combining by carefully matching the TWTs and other RF components for amplitude and phase over the entire frequency range.

The dB-3911 provides superior reliability, as all high-voltage power supplies are designed and manufactured in-house. dB Control utilizes the proprietary transformer fabrication, encapsulation and high-voltage potting techniques it has developed specifically for demanding military applications.

The power supply section of the dB-3911 employs a modular architecture and low-noise power supply topology using high-efficiency solid state power-conversion circuits. An embedded microcontroller provides the interface, control and protection functions, as well as extensive fault diagnostics and status indication.

With only one RF input and one RF output (similar to single TWT configurations), the dB-3911 is extremely easy to operate; no RF switches are required.

Features

- 3.4kW/4.0kW peak typical, 6% duty, 7.5 to 18 GHz
- Excellent amplitude and phase stability
- Very low phase noise
- Low harmonics and spurious
- Complete protection for the TWT and power supply against excessive currents, high VSWR, over temperature, and over/under voltages
- Extensive BIT and status monitoring
- Local or remote operation
- Fault isolation
- Optional remote protocol

Applications

- Test and measurement
- RFI/EMI/EMC testing
- Antenna pattern and radar cross-section measurements
- Electronic countermeasures (ECM)
- Electronic warfare (EW) simulation

dB-3911 TWT Amplifier Specifications

Reliability by Design®

Electrical

Frequency Range	7.5 GHz to 18.0 GHz, instantaneous bandwidth
Power Output	3.4kW from 7.5 to 11.0 GHz 4.0kW from 11.0 to 17.0 GHz 3.4kW from 17.0 to 18.0 GHz
Duty	6% max. P.W. 50 μ s max. PRF 100kHz max.
RF Input for Rated Output Power	0 dBm (1 milliwatt)
Harmonics	-10 dBc typical
Spurious	-50 dBc within 1 MHz of carrier
Input/Output VSWR Load	2.5:1 max.
VSWR	1.5:1 max. for full specification compliance 2.5:1 max. no damage
Prime Power	220 VAC, Single Phase, 50/60 Hz
Power Consumption	3 kVA max.
Amplifier Protection	TWT Over-Temperature, Helix Over-Current, Arc Protection, Cathode Over-Voltage, High Reflected RF Power, Power Supply Over-Temperature
Front Panel Digital Display	Equipment Status, Faults
RF Sample	Forward/Reflected Power, -60 dBc
Instrument Control	Local or remote
Front Panel Controls	Power On
Optional Protocols	RS232, RS422, RS485, Ethernet (TCP/IP) or custom protocols


Mechanical

Connectors:	
RF Input	Type N (F)
RF Output	WRD-750 Flange
RF Sample	SMA/Type N (F)
Remote Control	DB-15
Input Power Connector	MS Type (optional)
Interlock	DB-9
Dimensions	18" (W) x 21" (H) x 26.7" (D) max.
Weight	175 lbs, max.
Cooling	Built-In forced air

Environmental

Operating Temperature	-20° C to +50° C, ambient
Operating Altitude	Up to 10,000 feet above mean sea level
Humidity	Up to 95% RH non-condensing

Specifications subject to change without notice.



About dB Control

Established in 1990, dB Control Corp., a subsidiary of the Electronic Technologies Group (ETG) of HEICO Corp., supplies mission-critical, often sole-source, products worldwide to military organizations, as well as to major defense contractors and commercial manufacturers. dB Control designs and manufactures reliable high-power TWT Amplifiers (TWTAs), microwave power modules (MPMs), transmitters and power supplies with modulators for radar, electronic countermeasures (ECM) and data link applications. The company's high-power amplifiers use solid state, as well as vacuum electron devices and cover the 1 to 50 GHz frequency range. The modularity of dB Control's designs enables rapid configuration of custom products for a variety of platforms, including ground-based and high-altitude military manned and unmanned aircraft. dB Control has an outstanding record of successfully repairing, refurbishing and replacing tightly packaged high-voltage transformers, assemblies and power supplies. The company offers specialized contract manufacturing, transformer winding and testing, full vacuum encapsulation, pressure cure, conformal coating and repair depot services from its modern 40,000 square foot facilities in Fremont, California. www.dBControl.com

dB Control
a HEICO company
Reliability by Design®

